



E I DUPONT DE NEMOURS & CO INC
 DUPONT POLYMERS, ENGINEERING POLYMERS
 NYLON RESINS PO BOX 80713, CHESTNUT RUN
 PLAZA, WILMINGTON DE 19880

E41938 (M)



Mil Dsg	Col	Min Thk mm	UL94 Flame Class	Elec	RTI		H W	H A	H V	D 4	C
					Mech with Imp	w/o Imp					
Polyamide, Type 66 nylon (PA66), designated "Zytel", furnished in the form of pellets.											
132F	All	0.71	94V-2	125	65	65	4	0	—	—	—
133L, 135F	All	1.5	94V-2	125	75	85	3	0	0	—	—
		3.0	94V-2	125	75	85	2	0	0	6	0
		6.0	94V-2	125	75	85	2	0	0	—	—
✓ 101(F2), 101F, 101L, E101L, E101(F1)	All	0.71	94V-2	125	65	65	4	0	—	—	—
		1.5	94V-2	125	75	85	3	0	0	—	—
101(F2), 101F, 101L, E101L, E101(F1)	All	3.0	94V-2	125	75	85	2	0	0	6	0
		6.0	94V-2	125	75	85	2	0	0	—	—
EFE1068	All	0.71	94V-2	125	65	65	4	0	—	—	—
		1.5	94V-2	125	75	85	3	0	0	—	—
		3.0	94V-2	125	75	85	2	0	0	6	0
		6.0	94V-2	125	75	85	2	0	0	—	—
EFE1030	All	0.71	94V-2	125	—	—	4	0	—	—	—
		1.5	94V-2	125	75	85	3	0	0	—	—
		3.0	94V-2	125	75	85	2	0	0	6	0
		6.0	94V-2	125	75	85	2	0	0	—	—
FE-3370	NC, GY	0.84	94HB	65	65	65	—	—	—	—	—
FE-3397	NC, GY	0.85	94HB	65	65	65	—	—	—	—	—

TOLERANCE:	
L ≤ 10	±0.2
10 < L ≤ 30	±0.3
30 < L ≤ 50	±0.5
50 < L ≤ 100	±0.7
100 < L ≤ 250	±1.2
ABOVE 250	±1.5

APPROVED BY	張道陽	87.8.21.
REVIEWED BY	蕭存桂	87.8.21.
DRAWN BY	蕭存桂	87.8.21.
MATERIAL: NYLON 66(UL)		
FLAME CLASS: 94V-2		
COLOR: NATURAL		

品固企業有限公司
 品基電子塑膠製品廠
 鑽隆有限公司
 PINGOOD ENTERPRISE CO., LTD.

PART NAME: LED 套 LED HOLDER	A	REV. 1
PART NO: LED-10	SIZE	SHEET 1 OF 1