

CERAMIC DISC CAPACITOR
CLASS I TEMPERATURE COMPENSATION

TS15

FEATURES

- Linear temperature coefficient of capacitance.
- High stability of capacitance.
- Low loss at wide ranfe of frequecy.

SPECIFICATIONS

OPERATING TEMPERATURE RANGE	-25°C TO + 85°C
RATED WORKING VOLTAGE	DC 50 V, 500 V
TEST VOLTAGE	3 times of the rated voltage
CAPACITANCE	Within the tolerance at 1 MHz, 1±0.2 Vrms. 25°C
Q FACTOR	At 1 MHz. 1±0.2Vrms. 25°C C≥30pFQ≥1,000 C<30pFQ≥400+20C (C:Rated capacitance)
INSULATION RESISTANCE	10,000 MΩmin.

Rated Volt. (VDC)	Temp. Char.	Capacitance		Dimensions (mm)		
		Range(pF)	Tolerance	D Ø max	T max	F
50	CH 0±60 PPM/°C (NPO)	0.5 ~ 47	±0.25pF & ±0.5pF (Under 10pF)	5.5	3.5	5.0
		50 ~ 75		6.5		
		82 ~ 100		7.5		
		120 ~ 150	±5% & ±10% (Over 10pF)	8.5		
		180 ~ 270	10.5			
		300 ~ 390	12.5			
50	SL +350 ~ -1000PPM/°C	10 ~120	±5%	5.5	3.5	5.0
		150 ~ 240		6.5		
		270 ~ 330	&	7.5		
		360 ~ 470	±10%	8.5		
		500 ~ 820		10.5		

CLASS II HIGH DIELECTRIC CONSTANT

FEATURES

- Large capacitance in small sizes.
- Non liner temperature coefficient of capacitance.

SPECIFICATIONS

RATED WORKING VOLTAGE	DC 50 V, 500 V
TEST VOLTAGE	2.5 times of the rated voltage
CAPACITANCE	Within the tolerance at 1 MHz, 1±0.2 Vrms. 25°C
DISSIPATION FACTOR (tanδ)	Y5P, Z5U : tanδ ≤2.5% Z5V : tanδ ≤ 5%
INSULATION RESISTANCE	10,000M Ω or 200M Ω uF, whichever is the smaller

Rated Volt. (VDC)	Temp. Char.	Capacitance		Dimensions (mm)		
		Range(pF)	Tolerance	D Ø max	T max	F
50	B ±10% (Y5P)	100 ~ 2000	±10% & ±20%	5.5	3.5	5.0
		2200 . 2700		6.5		
		3000 . 3300		7.5		
		3900 . 4700		8.5		
		5600 . 6800 10000		10.5		
50	E +22~-56% (Z5U)	2200 . 3300 4700 . 5000	±20%	5.5	3.5	5.0
		5600 . 6800 8200		6.5		
		10000	&	7.5		
		12000 . 15000	+80-20%	8.5		
		18000 . 20000 22000		10.5		
50	F +22~-82% (Z5V)	4700 . 5000	+80-20%	5.5	3.5	5.0
		10000 . 15000		6.5		
		18000 . 20000		7.5		
		22000 . 30000		8.5		
		33000 . 40000 47000		10.5		